

MECHANICAL DIMENSIONS	ELECTRICAL SPECIFICATION																																																																							
<p>PIN CONNECTION # 1 N.C or Comp.OUTPUT # 2 GND # 3 OUTPUT # 4 Vcc</p> <p>Recommended Soldering Pattern</p>	<table border="1"> <tr> <td>Frequency range</td> <td>0.75MHz to 800.000MHz All combination of Frequency range Vs. Package type might not be available ,please contact factory.</td> </tr> </table>		Frequency range	0.75MHz to 800.000MHz All combination of Frequency range Vs. Package type might not be available ,please contact factory.																																																																				
Frequency range	0.75MHz to 800.000MHz All combination of Frequency range Vs. Package type might not be available ,please contact factory.																																																																							
<p>OUTPUT WAVEFORM</p>	<table border="1"> <tr> <td>Frequency Stability vs. Temperature</td> <td>±0.5 ppm to ±5.0ppm</td> </tr> <tr> <td>vs. Supply Voltage</td> <td>±0.1 / ±0.3 ppm max / Vdd ± 5%</td> </tr> <tr> <td>vs. Load</td> <td>±0.2 ppm max /15pF ±10%</td> </tr> <tr> <td>vs. Aging</td> <td>±1.0 ppm max/ year</td> </tr> <tr> <td>Temperature Range Operating</td> <td>See Table 2</td> </tr> <tr> <td>Storage</td> <td>-55°C to 125°C</td> </tr> <tr> <td>Supply Voltage</td> <td>3.3V ± 5% 5.0V ± 5%</td> </tr> <tr> <td>Input Current 3.3 V , 5V</td> <td>24.000MHz ~ 800.000MHz 25mA max ~ 100mA max</td> </tr> </table>		Frequency Stability vs. Temperature	±0.5 ppm to ±5.0ppm	vs. Supply Voltage	±0.1 / ±0.3 ppm max / Vdd ± 5%	vs. Load	±0.2 ppm max /15pF ±10%	vs. Aging	±1.0 ppm max/ year	Temperature Range Operating	See Table 2	Storage	-55°C to 125°C	Supply Voltage	3.3V ± 5% 5.0V ± 5%	Input Current 3.3 V , 5V	24.000MHz ~ 800.000MHz 25mA max ~ 100mA max																																																						
Frequency Stability vs. Temperature	±0.5 ppm to ±5.0ppm																																																																							
vs. Supply Voltage	±0.1 / ±0.3 ppm max / Vdd ± 5%																																																																							
vs. Load	±0.2 ppm max /15pF ±10%																																																																							
vs. Aging	±1.0 ppm max/ year																																																																							
Temperature Range Operating	See Table 2																																																																							
Storage	-55°C to 125°C																																																																							
Supply Voltage	3.3V ± 5% 5.0V ± 5%																																																																							
Input Current 3.3 V , 5V	24.000MHz ~ 800.000MHz 25mA max ~ 100mA max																																																																							
<p>TEST CIRCUIT</p>	<table border="1"> <tr> <td rowspan="2">Output characteristics</td> <td>pecl</td> <td>lvds</td> </tr> <tr> <td>Voh Logic "1"</td> <td>Vdd-1.025v min. 1.43v typ.</td> </tr> <tr> <td></td> <td>Vol Logic "0"</td> <td>Vdd-1.620v max. 1.10v typ.</td> </tr> <tr> <td></td> <td>Rise Time Tr</td> <td>1.0 nsec max. 1.0 nsec max.</td> </tr> <tr> <td></td> <td>Fall Time Tf</td> <td>1.0 nsec min. 1.0 nsec min.</td> </tr> <tr> <td></td> <td>Duty Cycle</td> <td>50//50 ± 5% 50//50 ± 5%</td> </tr> <tr> <td></td> <td>Differential Output Vod(Lvds)</td> <td>330mV typ.</td> </tr> <tr> <td></td> <td>Offset Voltage Vos(Lvds)</td> <td>1.2V typ.</td> </tr> <tr> <td>Phase Noise (typical) 20MHz offset</td> <td colspan="2"> -80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz </td> </tr> <tr> <td>Frequency Adjustment</td> <td colspan="2">±3ppm min by internal trimmer</td> </tr> </table>		Output characteristics	pecl	lvds	Voh Logic "1"	Vdd-1.025v min. 1.43v typ.		Vol Logic "0"	Vdd-1.620v max. 1.10v typ.		Rise Time Tr	1.0 nsec max. 1.0 nsec max.		Fall Time Tf	1.0 nsec min. 1.0 nsec min.		Duty Cycle	50//50 ± 5% 50//50 ± 5%		Differential Output Vod(Lvds)	330mV typ.		Offset Voltage Vos(Lvds)	1.2V typ.	Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz		Frequency Adjustment	±3ppm min by internal trimmer																																										
Output characteristics	pecl	lvds																																																																						
	Voh Logic "1"	Vdd-1.025v min. 1.43v typ.																																																																						
	Vol Logic "0"	Vdd-1.620v max. 1.10v typ.																																																																						
	Rise Time Tr	1.0 nsec max. 1.0 nsec max.																																																																						
	Fall Time Tf	1.0 nsec min. 1.0 nsec min.																																																																						
	Duty Cycle	50//50 ± 5% 50//50 ± 5%																																																																						
	Differential Output Vod(Lvds)	330mV typ.																																																																						
	Offset Voltage Vos(Lvds)	1.2V typ.																																																																						
Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz																																																																							
Frequency Adjustment	±3ppm min by internal trimmer																																																																							
<p>PECL Levels Test Circuit</p> <p>LVDS Levels Test Circuit</p>	<p>ENVIROMENTAL & MECHANICAL SPECIFICATION</p> <table border="1"> <tr> <td>Shock</td> <td>MIL-STD-883C, Method 2002, Condition B</td> </tr> <tr> <td>Vibration</td> <td>MIL-STD-883C, Method 2007, Condition A</td> </tr> <tr> <td>Solderability</td> <td>MIL-STD-883C, Method 2003</td> </tr> <tr> <td>Seal integrity</td> <td>MIL-STD-883C, Method 1014, Condition C & A2</td> </tr> <tr> <td>Marking</td> <td>MIL-STD-202F, Method 215</td> </tr> </table> <table border="1"> <thead> <tr> <th colspan="2">TABLE1</th> <th colspan="4">TABLE2</th> </tr> <tr> <th>Symbol</th> <th>Stability</th> <th>Symbol</th> <th>Temp.</th> <th>Symbol</th> <th>Temp.</th> </tr> </thead> <tbody> <tr> <td>05</td> <td>±0.5ppm</td> <td>0</td> <td>0°C</td> <td>A</td> <td>50°C</td> </tr> <tr> <td>10</td> <td>±1.0ppm</td> <td>1</td> <td>-10°C</td> <td>B</td> <td>60°C</td> </tr> <tr> <td>15</td> <td>±1.5ppm</td> <td>2</td> <td>-20°C</td> <td>C</td> <td>70°C</td> </tr> <tr> <td>20</td> <td>±2.0ppm</td> <td>3</td> <td>-30°C</td> <td>D</td> <td>75°C</td> </tr> <tr> <td>25</td> <td>±2.5ppm</td> <td>4</td> <td>-40°C</td> <td>E</td> <td>80°C</td> </tr> <tr> <td>30</td> <td>±3.0ppm</td> <td></td> <td></td> <td>F</td> <td>85°C</td> </tr> <tr> <td>35</td> <td>±3.5ppm</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>50</td> <td>±5.0ppm</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		Shock	MIL-STD-883C, Method 2002, Condition B	Vibration	MIL-STD-883C, Method 2007, Condition A	Solderability	MIL-STD-883C, Method 2003	Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2	Marking	MIL-STD-202F, Method 215	TABLE1		TABLE2				Symbol	Stability	Symbol	Temp.	Symbol	Temp.	05	±0.5ppm	0	0°C	A	50°C	10	±1.0ppm	1	-10°C	B	60°C	15	±1.5ppm	2	-20°C	C	70°C	20	±2.0ppm	3	-30°C	D	75°C	25	±2.5ppm	4	-40°C	E	80°C	30	±3.0ppm			F	85°C	35	±3.5ppm					50	±5.0ppm				
Shock	MIL-STD-883C, Method 2002, Condition B																																																																							
Vibration	MIL-STD-883C, Method 2007, Condition A																																																																							
Solderability	MIL-STD-883C, Method 2003																																																																							
Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2																																																																							
Marking	MIL-STD-202F, Method 215																																																																							
TABLE1		TABLE2																																																																						
Symbol	Stability	Symbol	Temp.	Symbol	Temp.																																																																			
05	±0.5ppm	0	0°C	A	50°C																																																																			
10	±1.0ppm	1	-10°C	B	60°C																																																																			
15	±1.5ppm	2	-20°C	C	70°C																																																																			
20	±2.0ppm	3	-30°C	D	75°C																																																																			
25	±2.5ppm	4	-40°C	E	80°C																																																																			
30	±3.0ppm			F	85°C																																																																			
35	±3.5ppm																																																																							
50	±5.0ppm																																																																							