

MECHANICAL DIMENSIONS	ELECTRICAL SPECIFICATION																																																	
<p>PIN CONNECTION            # 1 N.C            # 2 GND            # 3 OUTPUT            # 4 Vcc</p>	<table border="1"> <tr> <td>Frequency range</td> <td>6.000MHz to 190.000MHz</td> </tr> </table>		Frequency range	6.000MHz to 190.000MHz																																														
Frequency range	6.000MHz to 190.000MHz																																																	
	<table border="1"> <tr> <td>Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging</td> <td>±0.5 ppm to ±5.0ppm ±0.1 / ±0.2 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year</td> </tr> </table>		Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging	±0.5 ppm to ±5.0ppm ±0.1 / ±0.2 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year																																														
Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging	±0.5 ppm to ±5.0ppm ±0.1 / ±0.2 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year																																																	
	<table border="1"> <tr> <td>Temperature Range Operating Storage</td> <td>See Table 2 -55°C to 125°C</td> </tr> </table>		Temperature Range Operating Storage	See Table 2 -55°C to 125°C																																														
Temperature Range Operating Storage	See Table 2 -55°C to 125°C																																																	
	<table border="1"> <tr> <td>Supply Voltage</td> <td>3.3V ± 5% 5.0V ± 5%</td> </tr> </table>		Supply Voltage	3.3V ± 5% 5.0V ± 5%																																														
Supply Voltage	3.3V ± 5% 5.0V ± 5%																																																	
	<table border="1"> <tr> <td>Input Current Clipped sinewave</td> <td>6.00MHz ~ 190.000MHz 2.0mA max ~ 30mA max</td> </tr> </table>		Input Current Clipped sinewave	6.00MHz ~ 190.000MHz 2.0mA max ~ 30mA max																																														
Input Current Clipped sinewave	6.00MHz ~ 190.000MHz 2.0mA max ~ 30mA max																																																	
	<table border="1"> <tr> <td>Output characteristics</td> <td>Clipped sinewave Level 3.3V 0.8Vp-p min 5.0V 1.0Vp-p min Load 10kΩ//10pF</td> </tr> </table>		Output characteristics	Clipped sinewave Level 3.3V 0.8Vp-p min 5.0V 1.0Vp-p min Load 10kΩ//10pF																																														
Output characteristics	Clipped sinewave Level 3.3V 0.8Vp-p min 5.0V 1.0Vp-p min Load 10kΩ//10pF																																																	
<p><b>OUTPUT WAVEFORM</b></p>	<table border="1"> <tr> <td>Phase Noise (typical) 20MHz offset</td> <td>-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz</td> </tr> </table>		Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz																																														
Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz																																																	
	<table border="1"> <tr> <td>Frequency Adjustment</td> <td>±3ppm min by internal trimmer</td> </tr> </table>		Frequency Adjustment	±3ppm min by internal trimmer																																														
Frequency Adjustment	±3ppm min by internal trimmer																																																	
	<p><b>ENVIROMENTAL &amp; MECHANICAL SPECIFICATION</b></p>																																																	
	<table border="1"> <tr> <td>Shock</td> <td>MIL-STD-883C, Method 2002, Condition B</td> </tr> <tr> <td>Vibration</td> <td>MIL-STD-883C, Method 2007, Condition A</td> </tr> <tr> <td>Solderability</td> <td>MIL-STD-883C, Method 2003</td> </tr> <tr> <td>Seal integrity</td> <td>MIL-STD-883C, Method 1014, Condition C &amp; A2</td> </tr> <tr> <td>Marking</td> <td>MIL-STD-202F, Method 215</td> </tr> </table>		Shock	MIL-STD-883C, Method 2002, Condition B	Vibration	MIL-STD-883C, Method 2007, Condition A	Solderability	MIL-STD-883C, Method 2003	Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2	Marking	MIL-STD-202F, Method 215																																						
Shock	MIL-STD-883C, Method 2002, Condition B																																																	
Vibration	MIL-STD-883C, Method 2007, Condition A																																																	
Solderability	MIL-STD-883C, Method 2003																																																	
Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2																																																	
Marking	MIL-STD-202F, Method 215																																																	
<p><b>TEST CIRCUIT</b></p>	<table border="1"> <tr> <th colspan="2">TABLE1</th> <th colspan="2">TABLE2</th> </tr> <tr> <th>Symbol</th> <th>Stability</th> <th>Symbol</th> <th>Temp.</th> </tr> </table>		TABLE1		TABLE2		Symbol	Stability	Symbol	Temp.																																								
TABLE1		TABLE2																																																
Symbol	Stability	Symbol	Temp.																																															
	<table border="1"> <tr> <td>05</td> <td>±0.5ppm</td> <td>0</td> <td>0°C</td> <td>A</td> <td>50°C</td> </tr> <tr> <td>10</td> <td>±1.0ppm</td> <td>1</td> <td>-10°C</td> <td>B</td> <td>60°C</td> </tr> <tr> <td>15</td> <td>±1.5ppm</td> <td>2</td> <td>-20°C</td> <td>C</td> <td>70°C</td> </tr> <tr> <td>20</td> <td>±2.0ppm</td> <td>3</td> <td>-30°C</td> <td>D</td> <td>75°C</td> </tr> <tr> <td>25</td> <td>±2.5ppm</td> <td>4</td> <td>-40°C</td> <td>E</td> <td>80°C</td> </tr> <tr> <td>30</td> <td>±3.0ppm</td> <td></td> <td></td> <td>F</td> <td>85°C</td> </tr> <tr> <td>35</td> <td>±3.5ppm</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>50</td> <td>±5.0ppm</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>		05	±0.5ppm	0	0°C	A	50°C	10	±1.0ppm	1	-10°C	B	60°C	15	±1.5ppm	2	-20°C	C	70°C	20	±2.0ppm	3	-30°C	D	75°C	25	±2.5ppm	4	-40°C	E	80°C	30	±3.0ppm			F	85°C	35	±3.5ppm					50	±5.0ppm				
05	±0.5ppm	0	0°C	A	50°C																																													
10	±1.0ppm	1	-10°C	B	60°C																																													
15	±1.5ppm	2	-20°C	C	70°C																																													
20	±2.0ppm	3	-30°C	D	75°C																																													
25	±2.5ppm	4	-40°C	E	80°C																																													
30	±3.0ppm			F	85°C																																													
35	±3.5ppm																																																	
50	±5.0ppm																																																	