



MECHANICAL DIMENSIONS	ELECTRICAL SPECIFICATION																																															
 <p>PIN CONNECTION #1 N.C #2 GND #3 OUTPUT #4 Vcc</p> <p>Recommended Soldering Pattern</p>	<table border="1"> <tr> <td>Frequency range</td> <td>10.000MHz to 40.000MHz Contact us if need high frequency</td> </tr> </table>		Frequency range	10.000MHz to 40.000MHz Contact us if need high frequency																																												
Frequency range	10.000MHz to 40.000MHz Contact us if need high frequency																																															
	<table border="1"> <tr> <td>Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging</td> <td>±0.5 ppm to ±5.0ppm ±0.2 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year</td> </tr> </table>		Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging	±0.5 ppm to ±5.0ppm ±0.2 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year																																												
Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging	±0.5 ppm to ±5.0ppm ±0.2 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year																																															
	<table border="1"> <tr> <td>Temperature Range Operating Storage</td> <td>See Table 2 -55°C to 125°C</td> </tr> </table>		Temperature Range Operating Storage	See Table 2 -55°C to 125°C																																												
Temperature Range Operating Storage	See Table 2 -55°C to 125°C																																															
	<table border="1"> <tr> <td>Supply Voltage</td> <td>3.3V ± 5% 5.0V ± 5%</td> </tr> </table>		Supply Voltage	3.3V ± 5% 5.0V ± 5%																																												
Supply Voltage	3.3V ± 5% 5.0V ± 5%																																															
	<table border="1"> <tr> <td>Input Current Clipped sinewave</td> <td>10.00MHz ~ 40.000MHz 2.0mA max ~ 4mA max</td> </tr> </table>		Input Current Clipped sinewave	10.00MHz ~ 40.000MHz 2.0mA max ~ 4mA max																																												
Input Current Clipped sinewave	10.00MHz ~ 40.000MHz 2.0mA max ~ 4mA max																																															
	<table border="1"> <tr> <td>Output characteristics</td> <td>Clipped sinewave Level 3.3V 0.8Vp-p min 5.0V 1.0Vp-p min Load 10kΩ//10pF</td> </tr> </table>		Output characteristics	Clipped sinewave Level 3.3V 0.8Vp-p min 5.0V 1.0Vp-p min Load 10kΩ//10pF																																												
Output characteristics	Clipped sinewave Level 3.3V 0.8Vp-p min 5.0V 1.0Vp-p min Load 10kΩ//10pF																																															
	<table border="1"> <tr> <td>Phase Noise (typical) 20MHz offset</td> <td>-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz</td> </tr> </table>		Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz																																												
Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz																																															
	<table border="1"> <tr> <td>Frequency Adjustment</td> <td>±3ppm min by internal trimmer (OPTION)</td> </tr> </table>		Frequency Adjustment	±3ppm min by internal trimmer (OPTION)																																												
Frequency Adjustment	±3ppm min by internal trimmer (OPTION)																																															
ENVIROMENTAL & MECHANICAL SPECIFICATION																																																
Shock	MIL-STD-883C, Method 2002, Condition B																																															
Vibration	MIL-STD-883C, Method 2007, Condition A																																															
Solderability	MIL-STD-883C, Method 2003																																															
Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2																																															
Marking	MIL-STD-202F, Method 215																																															
TEST CIRCUIT	TABLE1	TABLE2																																														
	<table border="1"> <thead> <tr> <th>Symbol</th> <th>Stability</th> </tr> </thead> <tbody> <tr><td>05</td><td>±0.5ppm</td></tr> <tr><td>10</td><td>±1.0ppm</td></tr> <tr><td>15</td><td>±1.5ppm</td></tr> <tr><td>20</td><td>±2.0ppm</td></tr> <tr><td>25</td><td>±2.5ppm</td></tr> <tr><td>30</td><td>±3.0ppm</td></tr> <tr><td>35</td><td>±3.5ppm</td></tr> <tr><td>50</td><td>±5.0ppm</td></tr> </tbody> </table>	Symbol	Stability	05	±0.5ppm	10	±1.0ppm	15	±1.5ppm	20	±2.0ppm	25	±2.5ppm	30	±3.0ppm	35	±3.5ppm	50	±5.0ppm	<table border="1"> <thead> <tr> <th>Symbol</th> <th>Temp.</th> <th>Symbol</th> <th>Temp.</th> </tr> </thead> <tbody> <tr><td>0</td><td>0°C</td><td>A</td><td>50°C</td></tr> <tr><td>1</td><td>-10°C</td><td>B</td><td>60°C</td></tr> <tr><td>2</td><td>-20°C</td><td>C</td><td>70°C</td></tr> <tr><td>3</td><td>-30°C</td><td>D</td><td>75°C</td></tr> <tr><td>4</td><td>-40°C</td><td>E</td><td>80°C</td></tr> <tr><td></td><td></td><td>F</td><td>85°C</td></tr> </tbody> </table>	Symbol	Temp.	Symbol	Temp.	0	0°C	A	50°C	1	-10°C	B	60°C	2	-20°C	C	70°C	3	-30°C	D	75°C	4	-40°C	E	80°C			F	85°C
Symbol	Stability																																															
05	±0.5ppm																																															
10	±1.0ppm																																															
15	±1.5ppm																																															
20	±2.0ppm																																															
25	±2.5ppm																																															
30	±3.0ppm																																															
35	±3.5ppm																																															
50	±5.0ppm																																															
Symbol	Temp.	Symbol	Temp.																																													
0	0°C	A	50°C																																													
1	-10°C	B	60°C																																													
2	-20°C	C	70°C																																													
3	-30°C	D	75°C																																													
4	-40°C	E	80°C																																													
		F	85°C																																													