

MECHANICAL DIMENSIONS	ELECTRICAL SPECIFICATION																																													
<p>PIN CONNECTION</p> <ul style="list-style-type: none"> #1 N.C #2 GND #3 OutPut #4 Vcc <p>Recommended soldering pattern</p>	<p>Frequency range</p>	<p>10.000MHz to 27.000MHz</p>																																												
<p>OUTPUT WAVEFORM</p>	<p>Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging</p>	<p>±1.0 ppm to ±5.0ppm ±0.2 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year</p>																																												
<p>TEST CIRCUIT</p> <p>C1 : 10nF CL: 10kohm//10pF</p>	<p>Temperature Range Operating Storage</p>	<p>See Table 2 -55℃ to 125℃</p>																																												
	<p>Supply Voltage</p>	<p>2.8V ~3.3V , 5.0V (± 5%)</p>																																												
	<p>Input Current</p>	<p>2.0mA 10.000MHz to 27.000MHz</p>																																												
	<p>Output characteristics Clipped sinewave</p>	<p>Level 3.0V 0.8Vp-p min Level 5.0V 1.0Vp-p min Load 10kΩ//10pF Phase Noise (typical) 20MHz offset</p> <p>-80 dBc / Hz @ 10Hz -110 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz</p>																																												
	ENVIROMENTAL & MECHANICAL SPECIFICATION																																													
	<p>Shock Vibration Solderability Seal integrity Marking</p>	<p>MIL-STD-883C, Method 2002, Condition B MIL-STD-883C, Method 2007, Condition A MIL-STD-883C, Method 2003 MIL-STD-883C, Method 1014, Condition C & A2 MIL-STD-202F, Method 215</p>																																												
	TABLE1	TABLE2																																												
	<table border="1"> <thead> <tr> <th>Symbol</th> <th>Stability</th> </tr> </thead> <tbody> <tr><td>10</td><td>±1.0ppm</td></tr> <tr><td>15</td><td>±1.5ppm</td></tr> <tr><td>20</td><td>±2.0ppm</td></tr> <tr><td>25</td><td>±2.5ppm</td></tr> <tr><td>30</td><td>±3.0ppm</td></tr> <tr><td>35</td><td>±3.5ppm</td></tr> <tr><td>50</td><td>±5.0ppm</td></tr> </tbody> </table>	Symbol	Stability	10	±1.0ppm	15	±1.5ppm	20	±2.0ppm	25	±2.5ppm	30	±3.0ppm	35	±3.5ppm	50	±5.0ppm	<table border="1"> <thead> <tr> <th>Symbol</th> <th>Temp.</th> <th>Symbol</th> <th>Temp.</th> </tr> </thead> <tbody> <tr><td>0</td><td>0℃</td><td>A</td><td>50℃</td></tr> <tr><td>1</td><td>-10℃</td><td>B</td><td>60℃</td></tr> <tr><td>2</td><td>-20℃</td><td>C</td><td>70℃</td></tr> <tr><td>3</td><td>-30℃</td><td>D</td><td>75℃</td></tr> <tr><td>4</td><td>-40℃</td><td>E</td><td>80℃</td></tr> <tr><td></td><td></td><td>F</td><td>85℃</td></tr> </tbody> </table>	Symbol	Temp.	Symbol	Temp.	0	0℃	A	50℃	1	-10℃	B	60℃	2	-20℃	C	70℃	3	-30℃	D	75℃	4	-40℃	E	80℃			F	85℃
Symbol	Stability																																													
10	±1.0ppm																																													
15	±1.5ppm																																													
20	±2.0ppm																																													
25	±2.5ppm																																													
30	±3.0ppm																																													
35	±3.5ppm																																													
50	±5.0ppm																																													
Symbol	Temp.	Symbol	Temp.																																											
0	0℃	A	50℃																																											
1	-10℃	B	60℃																																											
2	-20℃	C	70℃																																											
3	-30℃	D	75℃																																											
4	-40℃	E	80℃																																											
		F	85℃																																											