

MECHANICAL DIMENSIONS	ELECTRICAL SPECIFICATION																																																	
	<table border="1"> <tr> <td>Frequency range</td> <td colspan="2">0.75MHz to 800.000MHz All combination of Frequency range Vs. Package type might not be available ,please contact factory.</td> </tr> <tr> <td>Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging</td> <td colspan="2">±0.5 ppm to ±5.0ppm ±0.1 / ±0.3 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year</td> </tr> <tr> <td>Temperature Range Operating Storage</td> <td colspan="2">See Table 2 -55°C to 125°C</td> </tr> <tr> <td>Supply Voltage</td> <td colspan="2">3.3V ± 5% 5.0V ± 5%</td> </tr> <tr> <td>Input Current 3.3 V , 5V</td> <td colspan="2">24.000MHz ~ 800.000MHz 25mA max ~ 100mA max</td> </tr> <tr> <td>Output characteristics</td> <td colspan="2"> <table border="1"> <thead> <tr> <th></th> <th>pecl</th> <th>lvds</th> </tr> </thead> <tbody> <tr> <td>Voh Logic "1"</td> <td>Vdd-1.025v min.</td> <td>1.43v typ.</td> </tr> <tr> <td>Vol Logic "0"</td> <td>Vdd-1.620v max.</td> <td>1.10v typ.</td> </tr> <tr> <td>Rise Time Tr</td> <td>1.0 nsec max.</td> <td>1.0 nsec max.</td> </tr> <tr> <td>Fall Time Tf</td> <td>1.0 nsec min.</td> <td>1.0 nsec min.</td> </tr> <tr> <td>Duty Cycle</td> <td>50//50 ± 5%</td> <td>50//50 ± 5%</td> </tr> <tr> <td>Differential Output Vod(Lvds)</td> <td></td> <td>330mV typ.</td> </tr> <tr> <td>Offset Voltage Vos(Lvds)</td> <td></td> <td>1.2V typ.</td> </tr> </tbody> </table> </td> </tr> <tr> <td>Phase Noise (typical) 20MHz offset</td> <td colspan="2">                     -80 dBc / Hz @ 10Hz                      -120 dBc / Hz @ 100Hz                      -135 dBc / Hz @ 1KHz                      -140 dBc / Hz @ 10KHz                      -145 dBc / Hz @100KHz                 </td> </tr> <tr> <td>Frequency Adjustment</td> <td colspan="2">±3ppm min by internal trimmer</td> </tr> </table>		Frequency range	0.75MHz to 800.000MHz All combination of Frequency range Vs. Package type might not be available ,please contact factory.		Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging	±0.5 ppm to ±5.0ppm ±0.1 / ±0.3 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year		Temperature Range Operating Storage	See Table 2 -55°C to 125°C		Supply Voltage	3.3V ± 5% 5.0V ± 5%		Input Current 3.3 V , 5V	24.000MHz ~ 800.000MHz 25mA max ~ 100mA max		Output characteristics	<table border="1"> <thead> <tr> <th></th> <th>pecl</th> <th>lvds</th> </tr> </thead> <tbody> <tr> <td>Voh Logic "1"</td> <td>Vdd-1.025v min.</td> <td>1.43v typ.</td> </tr> <tr> <td>Vol Logic "0"</td> <td>Vdd-1.620v max.</td> <td>1.10v typ.</td> </tr> <tr> <td>Rise Time Tr</td> <td>1.0 nsec max.</td> <td>1.0 nsec max.</td> </tr> <tr> <td>Fall Time Tf</td> <td>1.0 nsec min.</td> <td>1.0 nsec min.</td> </tr> <tr> <td>Duty Cycle</td> <td>50//50 ± 5%</td> <td>50//50 ± 5%</td> </tr> <tr> <td>Differential Output Vod(Lvds)</td> <td></td> <td>330mV typ.</td> </tr> <tr> <td>Offset Voltage Vos(Lvds)</td> <td></td> <td>1.2V typ.</td> </tr> </tbody> </table>			pecl	lvds	Voh Logic "1"	Vdd-1.025v min.	1.43v typ.	Vol Logic "0"	Vdd-1.620v max.	1.10v typ.	Rise Time Tr	1.0 nsec max.	1.0 nsec max.	Fall Time Tf	1.0 nsec min.	1.0 nsec min.	Duty Cycle	50//50 ± 5%	50//50 ± 5%	Differential Output Vod(Lvds)		330mV typ.	Offset Voltage Vos(Lvds)		1.2V typ.	Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz		Frequency Adjustment	±3ppm min by internal trimmer	
Frequency range	0.75MHz to 800.000MHz All combination of Frequency range Vs. Package type might not be available ,please contact factory.																																																	
Frequency Stability vs. Temperature vs. Supply Voltage vs. Load vs. Aging	±0.5 ppm to ±5.0ppm ±0.1 / ±0.3 ppm max / Vdd ± 5% ±0.2 ppm max /15pF ±10% ±1.0 ppm max/ year																																																	
Temperature Range Operating Storage	See Table 2 -55°C to 125°C																																																	
Supply Voltage	3.3V ± 5% 5.0V ± 5%																																																	
Input Current 3.3 V , 5V	24.000MHz ~ 800.000MHz 25mA max ~ 100mA max																																																	
Output characteristics	<table border="1"> <thead> <tr> <th></th> <th>pecl</th> <th>lvds</th> </tr> </thead> <tbody> <tr> <td>Voh Logic "1"</td> <td>Vdd-1.025v min.</td> <td>1.43v typ.</td> </tr> <tr> <td>Vol Logic "0"</td> <td>Vdd-1.620v max.</td> <td>1.10v typ.</td> </tr> <tr> <td>Rise Time Tr</td> <td>1.0 nsec max.</td> <td>1.0 nsec max.</td> </tr> <tr> <td>Fall Time Tf</td> <td>1.0 nsec min.</td> <td>1.0 nsec min.</td> </tr> <tr> <td>Duty Cycle</td> <td>50//50 ± 5%</td> <td>50//50 ± 5%</td> </tr> <tr> <td>Differential Output Vod(Lvds)</td> <td></td> <td>330mV typ.</td> </tr> <tr> <td>Offset Voltage Vos(Lvds)</td> <td></td> <td>1.2V typ.</td> </tr> </tbody> </table>			pecl	lvds	Voh Logic "1"	Vdd-1.025v min.	1.43v typ.	Vol Logic "0"	Vdd-1.620v max.	1.10v typ.	Rise Time Tr	1.0 nsec max.	1.0 nsec max.	Fall Time Tf	1.0 nsec min.	1.0 nsec min.	Duty Cycle	50//50 ± 5%	50//50 ± 5%	Differential Output Vod(Lvds)		330mV typ.	Offset Voltage Vos(Lvds)		1.2V typ.																								
	pecl	lvds																																																
Voh Logic "1"	Vdd-1.025v min.	1.43v typ.																																																
Vol Logic "0"	Vdd-1.620v max.	1.10v typ.																																																
Rise Time Tr	1.0 nsec max.	1.0 nsec max.																																																
Fall Time Tf	1.0 nsec min.	1.0 nsec min.																																																
Duty Cycle	50//50 ± 5%	50//50 ± 5%																																																
Differential Output Vod(Lvds)		330mV typ.																																																
Offset Voltage Vos(Lvds)		1.2V typ.																																																
Phase Noise (typical) 20MHz offset	-80 dBc / Hz @ 10Hz -120 dBc / Hz @ 100Hz -135 dBc / Hz @ 1KHz -140 dBc / Hz @ 10KHz -145 dBc / Hz @100KHz																																																	
Frequency Adjustment	±3ppm min by internal trimmer																																																	
<h3>OUTPUT WAVEFORM</h3>	<h3>ENVIROMENTAL &amp; MECHANICAL SPECIFICATION</h3> <table border="1"> <tr> <td>Shock</td> <td>MIL-STD-883C, Method 2002, Condition B</td> </tr> <tr> <td>Vibration</td> <td>MIL-STD-883C, Method 2007, Condition A</td> </tr> <tr> <td>Solderability</td> <td>MIL-STD-883C, Method 2003</td> </tr> <tr> <td>Seal integrity</td> <td>MIL-STD-883C, Method 1014, Condition C &amp; A2</td> </tr> <tr> <td>Marking</td> <td>MIL-STD-202F, Method 215</td> </tr> </table>		Shock	MIL-STD-883C, Method 2002, Condition B	Vibration	MIL-STD-883C, Method 2007, Condition A	Solderability	MIL-STD-883C, Method 2003	Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2	Marking	MIL-STD-202F, Method 215																																						
Shock	MIL-STD-883C, Method 2002, Condition B																																																	
Vibration	MIL-STD-883C, Method 2007, Condition A																																																	
Solderability	MIL-STD-883C, Method 2003																																																	
Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2																																																	
Marking	MIL-STD-202F, Method 215																																																	
<h3>TEST CIRCUIT</h3>	<table border="1"> <thead> <tr> <th colspan="2">TABLE1</th> <th colspan="2">TABLE2</th> </tr> <tr> <th>Symbol</th> <th>Stability</th> <th>Symbol</th> <th>Temp.</th> </tr> </thead> <tbody> <tr> <td>05</td> <td>±0.5ppm</td> <td>0</td> <td>0°C</td> </tr> <tr> <td>10</td> <td>±1.0ppm</td> <td>A</td> <td>50°C</td> </tr> <tr> <td>15</td> <td>±1.5ppm</td> <td>B</td> <td>60°C</td> </tr> <tr> <td>20</td> <td>±2.0ppm</td> <td>C</td> <td>70°C</td> </tr> <tr> <td>25</td> <td>±2.5ppm</td> <td>D</td> <td>75°C</td> </tr> <tr> <td>30</td> <td>±3.0ppm</td> <td>E</td> <td>80°C</td> </tr> <tr> <td>35</td> <td>±3.5ppm</td> <td>F</td> <td>85°C</td> </tr> <tr> <td>50</td> <td>±5.0ppm</td> <td></td> <td></td> </tr> </tbody> </table>		TABLE1		TABLE2		Symbol	Stability	Symbol	Temp.	05	±0.5ppm	0	0°C	10	±1.0ppm	A	50°C	15	±1.5ppm	B	60°C	20	±2.0ppm	C	70°C	25	±2.5ppm	D	75°C	30	±3.0ppm	E	80°C	35	±3.5ppm	F	85°C	50	±5.0ppm										
TABLE1		TABLE2																																																
Symbol	Stability	Symbol	Temp.																																															
05	±0.5ppm	0	0°C																																															
10	±1.0ppm	A	50°C																																															
15	±1.5ppm	B	60°C																																															
20	±2.0ppm	C	70°C																																															
25	±2.5ppm	D	75°C																																															
30	±3.0ppm	E	80°C																																															
35	±3.5ppm	F	85°C																																															
50	±5.0ppm																																																	