

MECHANICAL DIMENSIONS		ELECTRICAL SPECIFICATION																																																																									
<table border="1"> <tr> <th>TYPE</th> <th>"H" SIZE</th> </tr> <tr> <td>PV205M</td> <td>5.1 MAX</td> </tr> <tr> <td>PV207M</td> <td>7.5 MAX</td> </tr> </table>		TYPE	"H" SIZE	PV205M	5.1 MAX	PV207M	7.5 MAX	<table border="1"> <tr> <td>Frequency range</td> <td colspan="3">6.000MHz to 190.000MHz</td> </tr> <tr> <td>Frequency Stability vs. Temperature vs. Aging</td> <td colspan="3">All combination of Frequency range Vs. Package type might not be available ,please contact factory</td> </tr> <tr> <td>Temperature Range Operating Storage</td> <td colspan="3">See Table 2 -55°C to 105°C</td> </tr> <tr> <td>Supply Voltage</td> <td colspan="3">3.3V ± 5% 5.0V ± 5%</td> </tr> <tr> <td>Input Current</td> <td></td> <td>3.3V</td> <td>5.0V</td> </tr> <tr> <td></td> <td>fo ≤ 25.000MHz</td> <td>15mA</td> <td>20mA</td> </tr> <tr> <td></td> <td>fo ≤ 50.000MHz</td> <td>25mA</td> <td>30mA</td> </tr> <tr> <td></td> <td>fo ≤ 80.000MHz</td> <td>35mA</td> <td>50mA</td> </tr> <tr> <td></td> <td>fo ≤ 125.000MHz</td> <td>40mA</td> <td>60mA</td> </tr> <tr> <td></td> <td>fo ≤ 190.000MHz</td> <td>45mA</td> <td>70mA</td> </tr> <tr> <td>Output characteristics</td> <td>Level</td> <td>3.3V</td> <td>Sinewave 0 dBm typ</td> </tr> <tr> <td></td> <td>5.0V</td> <td></td> <td>10 dBm typ</td> </tr> <tr> <td></td> <td>Load</td> <td colspan="2">50Ω</td> </tr> <tr> <td colspan="4">Pull Characteristics</td> </tr> <tr> <td>Pulling Range</td> <td colspan="3">±50ppm / ±100 / ±150 ppm min</td> </tr> <tr> <td>Control Range</td> <td colspan="3">Wide pulling range : contact company 1.65V ± 1.5V (Vdd : 3.3V) 2.5V ± 2.0V/2.5V (Vdd : 5.0V)</td> </tr> </table>				Frequency range	6.000MHz to 190.000MHz			Frequency Stability vs. Temperature vs. Aging	All combination of Frequency range Vs. Package type might not be available ,please contact factory			Temperature Range Operating Storage	See Table 2 -55°C to 105°C			Supply Voltage	3.3V ± 5% 5.0V ± 5%			Input Current		3.3V	5.0V		fo ≤ 25.000MHz	15mA	20mA		fo ≤ 50.000MHz	25mA	30mA		fo ≤ 80.000MHz	35mA	50mA		fo ≤ 125.000MHz	40mA	60mA		fo ≤ 190.000MHz	45mA	70mA	Output characteristics	Level	3.3V	Sinewave 0 dBm typ		5.0V		10 dBm typ		Load	50Ω		Pull Characteristics				Pulling Range	±50ppm / ±100 / ±150 ppm min			Control Range	Wide pulling range : contact company 1.65V ± 1.5V (Vdd : 3.3V) 2.5V ± 2.0V/2.5V (Vdd : 5.0V)		
TYPE	"H" SIZE																																																																										
PV205M	5.1 MAX																																																																										
PV207M	7.5 MAX																																																																										
Frequency range	6.000MHz to 190.000MHz																																																																										
Frequency Stability vs. Temperature vs. Aging	All combination of Frequency range Vs. Package type might not be available ,please contact factory																																																																										
Temperature Range Operating Storage	See Table 2 -55°C to 105°C																																																																										
Supply Voltage	3.3V ± 5% 5.0V ± 5%																																																																										
Input Current		3.3V	5.0V																																																																								
	fo ≤ 25.000MHz	15mA	20mA																																																																								
	fo ≤ 50.000MHz	25mA	30mA																																																																								
	fo ≤ 80.000MHz	35mA	50mA																																																																								
	fo ≤ 125.000MHz	40mA	60mA																																																																								
	fo ≤ 190.000MHz	45mA	70mA																																																																								
Output characteristics	Level	3.3V	Sinewave 0 dBm typ																																																																								
	5.0V		10 dBm typ																																																																								
	Load	50Ω																																																																									
Pull Characteristics																																																																											
Pulling Range	±50ppm / ±100 / ±150 ppm min																																																																										
Control Range	Wide pulling range : contact company 1.65V ± 1.5V (Vdd : 3.3V) 2.5V ± 2.0V/2.5V (Vdd : 5.0V)																																																																										
OUTPUT WAVEFORM 																																																																											
TEST CIRCUIT 		ENVIROMENTAL & MECHANICAL SPECIFICATION <table border="1"> <tr> <td>Shock</td> <td>MIL-STD-883C, Method 2002, Condition B</td> </tr> <tr> <td>Vibration</td> <td>MIL-STD-883C, Method 2007, Condition A</td> </tr> <tr> <td>Solderability</td> <td>MIL-STD-883C, Method 2003</td> </tr> <tr> <td>Seal integrity</td> <td>MIL-STD-883C, Method 1014, Condition C & A2</td> </tr> <tr> <td>Marking</td> <td>MIL-STD-202F, Method 215</td> </tr> </table>				Shock	MIL-STD-883C, Method 2002, Condition B	Vibration	MIL-STD-883C, Method 2007, Condition A	Solderability	MIL-STD-883C, Method 2003	Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2	Marking	MIL-STD-202F, Method 215																																																												
Shock	MIL-STD-883C, Method 2002, Condition B																																																																										
Vibration	MIL-STD-883C, Method 2007, Condition A																																																																										
Solderability	MIL-STD-883C, Method 2003																																																																										
Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2																																																																										
Marking	MIL-STD-202F, Method 215																																																																										
<table border="1"> <thead> <tr> <th colspan="2">TABLE1</th> <th colspan="2">TABLE2</th> </tr> <tr> <th>Symbol</th> <th>Stability</th> <th>Symbol</th> <th>Temp.</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>± 10ppm</td> <td>0</td> <td>0°C</td> </tr> <tr> <td>15</td> <td>± 15ppm</td> <td>A</td> <td>50°C</td> </tr> <tr> <td>20</td> <td>± 20ppm</td> <td>1</td> <td>-10°C</td> </tr> <tr> <td>30</td> <td>± 30ppm</td> <td>B</td> <td>60°C</td> </tr> <tr> <td>50</td> <td>± 50ppm</td> <td>2</td> <td>-20°C</td> </tr> <tr> <td>100</td> <td>±100ppm</td> <td>C</td> <td>70°C</td> </tr> <tr> <td></td> <td></td> <td>3</td> <td>-30°C</td> </tr> <tr> <td></td> <td></td> <td>D</td> <td>75°C</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td>-40°C</td> </tr> <tr> <td></td> <td></td> <td>E</td> <td>80°C</td> </tr> <tr> <td></td> <td></td> <td>F</td> <td>85°C</td> </tr> </tbody> </table>		TABLE1		TABLE2		Symbol	Stability	Symbol	Temp.	10	± 10ppm	0	0°C	15	± 15ppm	A	50°C	20	± 20ppm	1	-10°C	30	± 30ppm	B	60°C	50	± 50ppm	2	-20°C	100	±100ppm	C	70°C			3	-30°C			D	75°C			4	-40°C			E	80°C			F	85°C																						
TABLE1		TABLE2																																																																									
Symbol	Stability	Symbol	Temp.																																																																								
10	± 10ppm	0	0°C																																																																								
15	± 15ppm	A	50°C																																																																								
20	± 20ppm	1	-10°C																																																																								
30	± 30ppm	B	60°C																																																																								
50	± 50ppm	2	-20°C																																																																								
100	±100ppm	C	70°C																																																																								
		3	-30°C																																																																								
		D	75°C																																																																								
		4	-40°C																																																																								
		E	80°C																																																																								
		F	85°C																																																																								