

MECHANICAL DIMENSIONS	ELECTRICAL SPECIFICATION																									
<p>PIN CONNECTION #1 V.C #2 GND #3 OUTPUT #4 Vcc</p>	Frequency range	0.75MHz to 800.000MHz All combination of Frequency range Vs. Package type might not be available ,please contact factory																								
	Frequency Stability vs. Temperature vs. Aging	± 10 ppm to ±50ppm ±3.0 ppm max/ year																								
	Temperature Range Operating Storage	See Table 2 -55°C to 105°C																								
	Supply Voltage	3.3V ± 5% 5.0V ± 5%																								
	Input Current 3.3 V , 5V	24.000MHz ~ 800.000MHz 25mA max ~ 100mA max																								
	Output characteristics	<table border="1"> <thead> <tr> <th></th> <th>pecl</th> <th>lvds</th> </tr> </thead> <tbody> <tr> <td>Voh Logic "1"</td> <td>Vdd-1.025v min.</td> <td>1.43v typ.</td> </tr> <tr> <td>Vol Logic "0"</td> <td>Vdd-1.620v max.</td> <td>1.10v typ.</td> </tr> <tr> <td>Rise Time Tr</td> <td>1.0 nsec max.</td> <td>1.0 nsec max.</td> </tr> <tr> <td>Fall Time Tf</td> <td>1.0 nsec min.</td> <td>1.0 nsec min.</td> </tr> <tr> <td>Duty Cycle</td> <td>50//50 ± 5%</td> <td>50//50 ± 5%</td> </tr> <tr> <td>Differential Output Vod(Lvds)</td> <td></td> <td>330mV typ.</td> </tr> <tr> <td>Offset Voltage Vos(Lvds)</td> <td></td> <td>1.2V typ</td> </tr> </tbody> </table>		pecl	lvds	Voh Logic "1"	Vdd-1.025v min.	1.43v typ.	Vol Logic "0"	Vdd-1.620v max.	1.10v typ.	Rise Time Tr	1.0 nsec max.	1.0 nsec max.	Fall Time Tf	1.0 nsec min.	1.0 nsec min.	Duty Cycle	50//50 ± 5%	50//50 ± 5%	Differential Output Vod(Lvds)		330mV typ.	Offset Voltage Vos(Lvds)		1.2V typ
		pecl	lvds																							
	Voh Logic "1"	Vdd-1.025v min.	1.43v typ.																							
Vol Logic "0"	Vdd-1.620v max.	1.10v typ.																								
Rise Time Tr	1.0 nsec max.	1.0 nsec max.																								
Fall Time Tf	1.0 nsec min.	1.0 nsec min.																								
Duty Cycle	50//50 ± 5%	50//50 ± 5%																								
Differential Output Vod(Lvds)		330mV typ.																								
Offset Voltage Vos(Lvds)		1.2V typ																								
Pull Characteristics																										
Pulling Range	±50ppm / ±100 / ±150 ppm min Wide pulling range : contact company																									
Control Range	1.65V ± 1.5V (Vdd : 3.3V) 2.5V ± 2.5V (Vdd : 5.0V)																									

TEST CIRCUIT				ENVIROMENTAL & MECHANICAL SPECIFICATION			
<p>PECL Levels Test Circuit</p>		<p>LVDS Levels Test Circuit</p>		Shock	MIL-STD-883C, Method 2002, Condition B		
				Vibration	MIL-STD-883C, Method 2007, Condition A		
				Solderability	MIL-STD-883C, Method 2003		
				Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2		
				Marking	MIL-STD-202F, Method 215		
TABLE1		TABLE2					
Symbol	Stability	Symbol	Temp.	Symbol	Temp.		
10	± 10ppm	0	0°C	A	50°C		
15	± 15ppm	1	-10°C	B	60°C		
20	± 20ppm	2	-20°C	C	70°C		
30	± 30ppm	3	-30°C	D	75°C		
50	± 50ppm	4	-40°C	E	80°C		
100	±100ppm			F	85°C		